## TECHNICAL SPECIFICATIONS

SPECIFICATION	12			200	
		PASSION™ 3x 3-9x42	PASSION™ 3x 4-12x42	PASSION™ 3x 3-9x40i	PASSION™ 3x 4-12x50i
Magnification:		3x - 9x	4x - 12x	3x - 9x	4x - 12x
Field of view (FOV) ft at 100y:		44,67 - 16,6	34 - 14	36,2 - 12,1	36,2 - 12,1
Field of view (FOV) m at 100m:		14,8 - 5,5	11 - 4,5	12 - 4	10,4 - 3,2
Objective diameter (mm):	Effective diameter	42	42	40	50
Exit pupil diameter (mm):	Measurement of the pupilary ocular beam	14 - 4,7	11 - 3,5	13,3 - 4,5	10 -3,3
Eye Relief (inches):	From the last optical surface	3,74	3,74	3,54	3,54
Eye Relief (mm):	From the last optical surface	95	95	90	90
Travel value per click at 100y:	1 Click = $x/100y$	.25 (1/4")	.25 (1/4")	.25 (1/4")	.25 (1/4")
cm travel value per click at 100m:	1 Click = $x/100m$	0,7	0,7	0,7	0,7
Elevation range total (inches at 100y):	100y	72	61	50	50
Elevation range total (cm at 100m):	100m	200	170	140	140
Windage range total (cm at 100):	100m	200	170	140	140
Parallax compensation:	Parallax free at x distance	100 yds	100 yds	100 yds	100 yds
Transmission Daylight:	ISO 14490-5:2005	90%	90%	93%	93%
Height (inches):	Without covers	1,8	1,8	1,7	1,7
Height (mm):	Without covers	45	45	43,4	43,4
Width (inches):	Fully extended	1,8	1,8	2,4	2,4
Width (mm):	Fully extended	45	45	60	60
Length (inches):	At outside diameter	11,7	12,2	12,5	12,5
Length (mm):	At outside diameter	298	310	317	317
Tube diameter (mm):	Width of main tube	1"	1"	1"	1"
Weight (ounces):	Without covers	14,4	14,5	15,1	18,3
Weight (grams):	Without covers	410	413	430	520
Mechanical outer diameter (objective mm):	Obejctive end of scope	49,5	49,5	47,5	60
Mechanical outer diameter (ocular mm):	Ocular end of scope	42,5	42,5	41	41
Recticle Option:		Plex	Plex	G4i (German #4 illuminated)	G4i (German #4 illuminated)
Accessories inluded with this purchase:		instruction manual, cleaning cloth,			
		bikini scope cover	bikini scope cover	bikini scope cover, battery CR2032	bikini scope cover, battery CR2032
					7